

import recipients - gzipped file

Description

1. Create a new group. Import members from [gzipped XML file](#) file
2. Create a new group. Import members from [gzipped CSV file](#) file

See also [sync-mode](#) and [sync-qualifiers](#)

Example request with 2000members.xml.gz

```
<control request-id="TestGroup1" group-id="new"
  xmlns="http://webservices.ecircle-ag.com/ecm">
  <group-definition preferred-channel="email">
    <name>TestGroup2</name>
    <email-channel>
      <email>TestGroup1@qamanual.staging11.
shortest-route.com</email>
    </email-channel>
  </group-definition>
  <member-list add-mode="add_no_message" sync-
mode="update_mode">
    <uri-reference>2000members.xml.gz</uri-
reference>
  </member-list>
  <failure-report-address xmlns="
http://webservices.ecircle-ag.com/ecm">
    <email>saduser@mapp.com</email>
  </failure-report-address>
</control>
```

Example request recipients120.csv.gz

```
<control request-id="TestGroup3" group-id="new"
  xmlns="http://webservices.ecircle-ag.com/ecm">
  <group-definition preferred-channel="email">
    <name>TestGroup3</name>
    <email-channel>
      <email>TestGroup3@qamanual.staging11.
shortest-route.com</email>
    </email-channel>
  </group-definition>
  <member-list add-mode="add_no_message" sync-
mode="add" data-format="csv">
    <uri-reference>recipients120.csv.gz</uri-
reference>
  </member-list>
</control>
```

Example request recipients120.csv.gz - group update

```
<control
  xmlns="http://webservices.ecircle-ag.com
/ecm" request-id="1111" group-id="2505">
  <member-list sync-mode="add" data-format="
csv" >
    <uri-reference>cid:recipients11.
csv.gz</uri-reference>
  </member-list>
  <success-report-address>
    <email>happy.user@test.com</email>
  </success-report-address>
  <failure-report-address>
    <email>sad.user@test.com</email>
  </failure-report-address>
</control>
```