

# create a group

## Example request 1

```
<control xmlns="http://webservices.ecircle-ag.com
/ecm" request-id="newgroup123" group-id="new">
  <group-definition group-category-name="
category">
    <name>New Group</name>
    <description>New Group</description>
    <isocountry>GB</isocountry>
    <isolanguage>en</isolanguage>
    <email-channel>
      <email>newgroup@qamanual.staging11.
shortest-route.com</email>
      <from-handling>
        <special>
          <email>clonecontact@qamanual.
staging11.shortest-route.com</email>
          <name>Clone Master</name>
        </special>
      </from-handling>
      <reply-to-handling>
        <special>
          <email>reply-test@qamanual.
staging11.shortest-route.com</email>
          <name>Contact</name>
        </special>
      </reply-to-handling>
    </email-channel>
    <io-control>
      <sendout-speed>50000</sendout-speed>
    </io-control>
  </group-definition>
  <failure-report-address xmlns="
http://webservices.ecircle-ag.com/ecm">
    <email>saduser@mapp.com</email>
  </failure-report-address>
</control>
```

## Example request 2

```
<control
  xmlns="http://webservices.ecircle-ag.com/ecm"
  request-id="newgroup123" group-id="new">
  <group-definition preferred-channel="email">
    <name>{GROUP NAME}</name>
    <description>{GROUP DESCRIPTION}<
/description>
    <isocountry>{GROUP COUNTRY CODE}<
/isocountry>
    <isolanguage>{GROUP LANGUAGE CODE}<
/isolanguage>
    <redirection-link>{REDIRECTION LINK}<
/redirection-link>
    <redirection-timeout>7</redirection-
timeout>
    <email-channel>
      <email>{GROUP EMAIL - should end with
the domain name of the eC-m system}</email>
      <from-handling>
        <special>
          <email>{GROUP FROM ADDRESS}<
/email>
          <name>
            <![CDATA[{GROUP FROM
NAME}]]>
          </name>
        </special>
      </from-handling>
      <reply-to-handling>
        <special>
          <email>{REPLY ADDRESS}</email>
          <name>{REPLY NAME}</name>
        </special>
      </reply-to-handling>
    </email-channel>
    <tracking>
      <text link="true"/>
      <html reader="true" pixel-position="
top" link="true" individual-link="true"/>
    </tracking>
    <io-control>
      <requires-password />
      <sendout-speed>250000</sendout-speed>
      <bounce count="1" hours="168" />
      <!--Configure bounce settings for the
group-->
      <!--OR-->
      <!--
        <bounce count="3" category="transient"
hours="336" /><bounce count="2" category="blocked"
hours="336" /><bounce count="1" category="
rejected" hours="24" /><bounce count="2" category="
unknown" hours="336" />
      -->
    </io-control>
  </group-definition>
</control>
```