

message sendTransactional

Description

Sends a prepared message as a transactional message.
Attachments can be encoded using [base64encode.org](#)

Available from
v1

Request path

POST [REST URL]/message/sendTransactional

Query Parameters

Parameter	Type	Description
recipientId	Long	ID of the user
messageId	Long	ID of the message or prepared message
externalTransactionFormula	String	External transactional identifier. If not available, "null" can be used.
senderProfile	String	TLS sender profile. Requires a Feature Switch and setting up a profile name in Mapp Engage. (optional)

Request Body Type

[MessageContent](#) additionalContent

Example body

```
{
  "parameters":
    [{"name" : "Parameter
Name 1", "value" :
"Parameter Value 1"},
    {"name" : "Parameter
Name 2", "value":
"Parameter Value 2"}],
  "attachments":
    [{"name" :
"twitter_logo.png",
"contentType" :
"image/png",
"content":
"iVBORw0KGgoAAAANSUhEUGAAAB
UAAAARCAyAAAAyhueAAAAAGXRFW
HRTb2Z0d2FyZQBZG9iZSBjbWFn
ZVJlYWRScc1lPAAASFJREFUeNq
s1M0NgkAQhRdiAdiAgQ6468E01I
NntQ0pwFABdqBe9aAdiI13twS1A
bECfJPMkhVZftSXjJPsdh87z2Ws
NE1Fb3d3z+P0VVQIdQ5ShJhqywd
EgEgQQ1qwutsbFT4QM4DXFcALwi
3YJqDD2bPx4/PgCg
/OsW46NwAFA0nU7d70bUYAHxF+w
YMDUU8jiz19aG9TihEbyUS3oSav
NmoT5Sm1thA
/CkCLsvJ0In5XdnsIKkv+gCaSGZ
Q8QF7+AXrST0peBH8Ar9+grKfuS
1Mgd/wBjb
/0lmChvmBr14GgMy5qoiA
/N+zCPSNfPN2fCoVF86KLDQxqvc
93t18DaBxALcAi
/qLqKuaWpa1Affs0z8iB4ZRSzYI
ymNJLgAEAYsJkJ0LW
//gAAAAASUVORK5CYII="}]
}
```

Successful response

```
HTTP 204
```